



**KOYO K25X30X20H needle roller bearings**



K25X30X20H Bearing 2D drawings and 3D CAD models

Bearing No. K25X30X20H

Bore Diameter	25 mm
Outer Diameter	30 mm
Fw	25 mm
Ew	30 mm
Bc	20 mm
Weight	0.019 Kg
Basic dynamic load rating (C)	21.9 kN
Basic static load rating (C0)	36.1 kN
(Grease) Lubrication Speed	11000 r/min
(Oil) Lubrication Speed	17000 r/min
Category	Needle Non Thrust Roller Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.024
EAN	0060579021299
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly Only
Enclosure	Not Applicable
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	Not Applicable



## BEARING MANUFACTURING DE MEXICO, S.A.D...

Inch - Metric	Metric
Thrust Bearing	No
Long Description	25MM Bore; 30MM Outside Diameter; 20MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Other Features	Radial Roller   Hardened Steel Cage
Category	Needle Non Thrust Roller Bearing
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Manufacturer Item Number	K25X30X20H
Weight / LBS	0.042
Width	0.787 Inch   20 Millimeter
Bore	0.984 Inch   25 Millimeter
Outside Diameter	1.181 Inch   30 Millimeter
Bearing No.	K25X30X20H
Cr	21.9
C0r	36.1
Cu	5.65
Grease lub.	11000
Oil lub.	17000
P/S	S
(Refer.) Mass(kg)	0.019
Shaft(max.)	25.000
Shaft(min.)	24.991
Housing(max.)	30.020
Housing(min.)	30.007



**BEARING MANUFACTURING DE MEXICO,S.A.D...**